STRAINER

DUCTILE IRON | PN-25 (Y Type)

DESIGN & COMPLIANCES
EN 13789, BS 5152, BS 7350, EN 558-1(1), DIN 3352

END CONNECTION
BS EN 1092-2, BS 4504, DIN 2501

TESTING STANDARD
6755, EN 12266-1

APPLICATIONS
Water Supply, Oil, Gas, Steam, Raw Water, Waste Water



Sr. No	COMPONENTS	SPECIFICATIONS
1	Body	Ductile Iron EN-GJS-500
2	Cover	Ductile Iron EN-GJS-500
3	Perforated Mesh	SS 304 | SS 316
4	Gasket	Non Asbestos
Painting		Epoxy | Corrosion Resistant | Polyurethane

Special Configurations (Subject to manufacturer's approval)

- Gasket Spiral Wound, Wire Woven
- Ball Valve on Top Plate

DIMENSIONS (MM)																
Sizes	**40**	**50**	**65**	**80**	**100**	**125**	**150**	**200**	**250**	**300**	**350**	**400**	**450**	**500**	**600**	**700**
Face to Face (L)	200	230	290	310	350	400	480	600	730	850	980	1100	1200	-	-	-
OD (D)	150	165	185	200	235	270	300	360	425	485	555	620	670	730	845	-
Height (H)	200	225	285	300	335	385	460	550	610	700	770	940	1060	1120	1280	-