

FLANGES

RAISED FACE

DESIGN & COMPLIANCES

BS 4504, EN 1092-1

APPLICATIONS

Connect valves with pipe, pipe fittings.

A = PCD Pinch Circle

D = Outer Dia

C = Raised Face Dia

B = Thickness

RF = Raised Face Thickness

F = Bolt Dia

N = No. of Holes



DIMENSIONS (MM) - RAISED FACE PN-10																	
Sizes	50	65	80	100	125	150	200	250	300	350	400	450	500	600	700	800	900
A	125	145	160	180	210	240	295	350	400	460	515	565	620	725	840	950	1050
D	165	185	200	220	250	285	340	395	445	505	565	615	670	780	895	1015	1115
C	102	122	138	162	188	212	268	320	370	430	482	532	585	685	800	905	1005
B	20	20	20	22	22	24	26	29	32	35	38	42	46	52	-	-	-
RF	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
F	18	18	18	18	18	22	22	22	22	22	26	26	26	30	30	33	33
N	4	8	8	8	8	8	8	12	12	16	16	20	20	20	24	24	28

DIMENSIONS (MM) - RAISED FACE PN-16																	
Sizes	50	65	80	100	125	150	200	250	300	350	400	450	500	600	700	800	900
A	125	145	160	180	210	240	295	350	400	460	515	565	620	725	840	950	1050
D	165	185	200	220	250	285	340	405	460	520	580	640	715	840	910	1025	1125
C	102	122	138	162	188	212	268	320	378	438	550	590	610	725	800	905	1005
B	20	20	20	22	22	24	26	29	32	35	38	42	46	52	-	-	-
RF	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
F	18	18	18	18	18	22	22	26	26	26	30	30	33	36	36	39	39
N	4	8	8	8	8	8	8	12	12	16	16	20	20	20	24	24	28